

COOL DRY HEAT

# Get Control.



## TAKE CHARGE OF ANY ENVIRONMENT.

- Stay within the ideal drying temperature zone
- Increase productivity on fire and mold remediation jobs
- Pre-cool dehumidifiers to increase low-grain performance
- Keep occupants comfortable during the drying process
- Dehumidify and control temperatures on new construction jobs

Wherever temperature and humidity control are needed - the EB1400 has an answer - all in one rugged, portable rotomolded package.

- **SIMPLE OPERATION** - Easy to use digital temperature control
- **INTERCHANGEABLE DUCT RINGS** - 8" duct rings for spot cooling, focused heating or air exchange
- **EASY MAINTENANCE** - One-step filter changes
- **MICROBAN® ANTIMICROBIAL PRODUCT PROTECTION** - Inhibits growth of bacteria, mold and mildew.



| SPECS                             |   |
|-----------------------------------|---|
| <b>Split-stream Airflow</b>       | Warm Output (Condenser) - 750 CFM<br>Cool Output (Evaporator) - 470 CFM |
| <b>Cooling</b>                    | 1 Ton cooling effectiveness*<br>(10,120 BTU/HR rated)                   |
| <b>Water Removal Capabilities</b> | 110* pints/day  |
| <b>Operating Conditions</b>       | 60° - 115° F  |
| <b>Controls</b>                   | Digital thermostat  |
| <b>Power 115V</b>                 | 11.7* amps  |
| <b>Safety Approval</b>            | ETL listed to UL 474 Standard   |
| <b>Dimensions (HxWxD)</b>         | 45" x 25" x 31"<br>(114.3 cm x 63.5 cm x 78.7 cm)                       |
| <b>Weight</b>                     | 185 lbs (83.9 kg)   |
| <b>Pump/Hose</b>                  | Built-in condensate pump with 40 ft. hose<br>*at 95 / 60% RH            |



For more information and a **FREE GIFT** go to  
[www.dri-eaz.com/EB1400/gift](http://www.dri-eaz.com/EB1400/gift)

